

General Purpose NPN Epitaxial Planar Transistor


BTD1616AM3

BV_{CEO}	60V
I_C	3A
$V_{CESAT(max)}$	150mV


Features

- High breakdown voltage, $BV_{CEO} \geq 60V$
- Large continuous collector current capability
- Low collector saturation voltage
- Pb-free lead plating and halogen-free package

Symbol




Outline



Ordering Information

Device	Package	Shipping
BTD1616AM3-0-T2-G	SOT-89 (Pb-free lead plating and halogen-free package)	1000 pcs / Tape & Reel





Absolute Maximum Ratings (Ta=25°C)

Parameter	Symbol	Limits	Unit
Collector-Base Voltage	V _{CBO}	120	V
Collector-Emitter Voltage	V _{CEO}	60	V
Emitter-Base Voltage	V _{EBO}	7	V
Collector Current (DC)	I _C	3	A
Collector Current (pulse)	I _{CP}	5	A
Base Current	I _B	0.3	A
Power Dissipation	P _d	0.6	W
		1.5 (Note 1)	W
		2.1 (Note 2)	W
Operating Junction and Storage Temperature Range	T _j ; T _{stg}	-55~+150	°C







Note : 1. When mounted on 25mm×25mm×1.6 mm FR-4 PCB with high coverage of single sided 1 oz copper, in still air condition
 2. When mounted on 50mm×50mm×1.6 mm FR-4 PCB with high coverage of single sided 1 oz copper, in still air condition

Characteristics (Ta=25°C)

Symbol	Min.	Typ.	Max.	Unit	Test Conditions
BV _{CBO}	120	-	-	V	I _C =50μA
BV _{CEO}	60	-	-	V	I _C =1mA
BV _{EBO}	7	-	-	V	I _E =50μA
I _{CBO}	-	-	100	nA	V _{CB} =120V
I _{EBO}	-	-	100	nA	V _{EB} =7V
*V _{CE(sat)}	-	98	150	mV	I _C =1A, I _B =50mA
*V _{CE(sat)}	-	131	200	mV	I _C =1A, I _B =20mA
*V _{BE(sat)}	-	-	1	V	I _C =1A, I _B =50mA
*V _{BE(on)}	600	-	700	mV	V _{CE} =2V, I _C =50mA
*h _{FE 1}	200	-	400	-	V _{CE} =2V, I _C =100mA
*h _{FE 2}	120	-	-	-	V _{CE} =2V, I _C =1A
f _T	100	-	-	MHz	V _{CE} =2V, I _C =100mA, f=100MHz
C _{ob}	-	11	18	pF	V _{CB} =10V, I _E =0A, f=1MHz
t _{on}	-	40	-	ns	V _{CC} =30V, I _C =1A, I _{B1} =-I _{B2} =33mA, R _L =30Ω
t _{stg}	-	500	-		
t _f	-	120	-		


*Pulse Test: Pulse Width ≤380μs, Duty Cycle≤2%

Typical Characteristics




Typical Characteristic Curves(Cont.)


On Voltage vs Collector Current




Power Derating Curves




Cutoff Frequency vs Collector Current




Capacitance Characteristics




Recommended soldering footprint



Reel Dimension




Carrier Tape Dimension



Recommended wave soldering condition

Product	Peak Temperature	Soldering Time
Pb-free devices	260 +0/-5 °C	5 +1/-1 seconds


Recommended temperature profile for IR reflow



Profile feature	Sn-Pb eutectic Assembly	Pb-free Assembly
Average ramp-up rate (T _{smax} to T _p)	3°C/second max.	3°C/second max.
Preheat		
-Temperature Min(T _{s min})	100°C	150°C
-Temperature Max(T _{s max})	150°C	200°C
-Time(t _{s min} to t _{s max})	60-120 seconds	60-180 seconds
Time maintained above:		
-Temperature (T _L)	183°C	217°C
- Time (t _L)	60-150 seconds	60-150 seconds
Peak Temperature(T _P)	240 +0/-5 °C	260 +0/-5 °C
Time within 5°C of actual peak temperature(tp)	10-30 seconds	20-40 seconds
Ramp down rate	6°C/second max.	6°C/second max.
Time 25 °C to peak temperature	6 minutes max.	8 minutes max.

Note : All temperatures refer to topside of the package, measured on the package body surface.

SOT-89 Dimension



DIM	Inches		Millimeters		DIM	Inches		Millimeters	
	Min.	Max.	Min.	Max.		Min.	Max.	Min.	Max.
A	0.1732	0.1811	4.40	4.60	F	0.0591	TYP	1.50	TYP
B	0.1551	0.1673	3.94	4.25	G	0.1181	TYP	3.00	TYP
C	0.0610	REF	1.55	REF	H	0.0551	0.0630	1.40	1.60
D	0.0906	0.1024	2.30	2.60	I	0.0138	0.0173	0.35	0.44
E	0.0126	0.0205	0.32	0.52					

Notes: 1.Controlling dimension: millimeters.
 2.Maximum lead thickness includes lead finish thickness, and minimum lead thickness is the minimum thickness of base material.
 3.If there is any question with packing specification or packing method, please contact your local CYStek sales office.

Material:

- Lead: Pure tin plated.
- Mold Compound: Epoxy resin family, flammability solid burning class: UL94V-0.

Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of CYStek.
- CYStek reserves the right to make changes to its products without notice.
- CYStek **semiconductor products are not warranted to be suitable for use in Life-Support Applications, or systems.**
- CYStek assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.