

P-Channel Enhancement Mode Power MOSFET


MTB015P10F3

BV _{DSS}	-100V
I _D @ V _{GS} =-10V, T _C =25°C	-107A
I _D @ V _{GS} =-10V, T _A =25°C	-8.6A
R _{DS(on)(TYP)} @ V _{GS} =-10V, I _D =-20A	11.6mΩ
R _{DS(on)(TYP)} @ V _{GS} =-4.5V, I _D =-15A	13.7mΩ


Features

- Simple Drive Requirement
- Repetitive Avalanche Rated
- Fast Switching Characteristic
- RoHS compliant package

Symbol




Outline



Ordering Information

Device	Package	Shipping
MTB015P10F3-0-T7-X	TO-263 (Pb-free lead plating and RoHS compliant package)	800 pcs / Tape & Reel



**Absolute Maximum Ratings** ($T_C=25^\circ\text{C}$, unless otherwise noted)

Parameter	Symbol	Limits	Unit	
Drain-Source Voltage	V_{DS}	-100	V	
Gate-Source Voltage	V_{GS}	± 20		
Continuous Drain Current @ $T_C=25^\circ\text{C}$, $V_{GS}=-10\text{V}$ (silicon limit)	I_D (Note 4)	-107	A	
Continuous Drain Current @ $T_C=25^\circ\text{C}$, $V_{GS}=-10\text{V}$ (package limit)		-84		
Continuous Drain Current @ $T_C=100^\circ\text{C}$, $V_{GS}=-10\text{V}$		-68		
Pulsed Drain Current (Note 3)	I_{DM}	-428		
Continuous Drain Current @ $T_A=25^\circ\text{C}$, $V_{GS}=10\text{V}$ (Note 2)	I_{DSM}	-8.6		
Continuous Drain Current @ $T_A=70^\circ\text{C}$, $V_{GS}=10\text{V}$ (Note 2)		-6.9		
Avalanche Current (Note 3)	I_{AS}	-107	mJ	
Avalanche Energy @ $L=0.1\text{mH}$, $I_D=-107\text{A}$, $V_{DD}=-50\text{V}$ (Note 3)	E_{AS}	572		
Repetitive Avalanche Energy @ $L=0.1\text{mH}$	E_{AR}	37.5		
Power Dissipation	$T_C=25^\circ\text{C}$ (Note 1)	P_D	375	W
	$T_C=125^\circ\text{C}$ (Note 1)		125	
Power Dissipation	$T_A=25^\circ\text{C}$ (Note 2)	P_{DSM}	2	
	$T_A=70^\circ\text{C}$ (Note 2)		1.3	
Operating Junction and Storage Temperature	T_j, T_{stg}	-55~+175	$^\circ\text{C}$	

Thermal Data

Parameter	Symbol	Value	Unit
Thermal Resistance, Junction-to-case, max	$R_{\theta JC}$	0.4	$^\circ\text{C}/\text{W}$
Thermal Resistance, Junction-to-ambient, max, $t \leq 10\text{s}$ (Note 2)	$R_{\theta JA}$	15	
Thermal Resistance, Junction-to-ambient, max		62	

- Note :
- The power dissipation P_D is based on $T_{J(MAX)}=175^\circ\text{C}$, using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used.
 - The value of $R_{\theta JA}$ is measured with the device mounted on 1 in² FR-4 board with 2 oz. copper, in a still air environment with $T_A=25^\circ\text{C}$. The power dissipation P_{DSM} is based on $R_{\theta JA}$ and the maximum allowed junction temperature of 150°C . The value in any given application depends on the user's specific board design, and the maximum temperature of 175°C may be used if the PCB allows it.
 - Repetitive rating, pulse width limited by junction temperature $T_{J(MAX)}=175^\circ\text{C}$. Ratings are based on low frequency and low duty cycles to keep initial $T_J=25^\circ\text{C}$.
 - Calculated continuous drain current based on maximum allowable junction temperature.
 - The maximum current limited by package is 84A.
 - The static characteristics are obtained using $<300\mu\text{s}$ pulses, duty cycle 0.5% maximum.
 - The $R_{\theta JA}$ is the sum of thermal resistance from junction to case $R_{\theta JC}$ and case to ambient.



Characteristics (Tc=25°C, unless otherwise specified)


Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Static					
BV _{DSS}	-100	-	-	V	V _{GS} =0V, I _D =-250μA
V _{GS(th)}	-1.0	-	-2.5		V _{DS} = V _{GS} , I _D =-250μA
G _{FS}	-	43	-	S	V _{DS} =-10V, I _D =-10A
I _{GSS}	-	-	±100	nA	V _{GS} =±20V
I _{DSS}	-	-	-1	μA	V _{DS} =-100V, V _{GS} =0V
	-	-	-25		V _{DS} =-80V, V _{GS} =0V, T _j =125°C
*R _{DS(ON)}	-	11.6	15	mΩ	V _{GS} =-10V, I _D =-20A
	-	13.7	18		V _{GS} =-4.5V, I _D =-15A
Dynamic					
*Q _g (V _{GS} =-10V)	-	176	264	nC	I _D =-90A, V _{DS} =-50V, V _{GS} =-10V
*Q _g (V _{GS} =-4.5V)	-	90	135		
*Q _{gs}	-	20	-		
*Q _{gd}	-	62	-		
*t _{d(ON)}	-	34.6	51.9	ns	V _{DS} =-50V, I _D =-90A, V _{GS} =-10V, R _G =1Ω
*t _r	-	35.8	53.7		
*t _{d(OFF)}	-	169	253.5		
*t _f	-	51	76.5		
C _{iss}	-	10103	-	pF	V _{GS} =0V, V _{DS} =-30V, f=1MHz
C _{oss}	-	593	-		
C _{rss}	-	161	-		
R _g	-	2.9	-		
Source-Drain Diode					
*I _S	-	-	-84	A	
*I _{SM}	-	-	-428		
*V _{SD}	-	-0.78	-1.2	V	I _S =-20A, V _{GS} =0V
*t _{rr}	-	29	-	ns	I _F =-20A, V _{GS} =0V, dI _F /dt=100A/μs
*Q _{rr}	-	70	-	nC	

*Pulse Test : Pulse Width ≤300μs, Duty Cycle ≤2%




Typical Characteristics


Typical Output Characteristics




Brekdown Voltage vs Junction Temperature




Static Drain-Source On-State resistance vs Drain Current




Reverse Drain Current vs Source-Drain Voltage



Static Drain-Source On-State Resistance vs Gate-Source Voltage




Drain-Source On-State Resistance vs Junction Temperature




Typical Characteristics(Cont.)


Capacitance vs Drain-to-Source Voltage




Threshold Voltage vs Junction Temperature




Forward Transfer Admittance vs Drain Current




Gate Charge Characteristics



Maximum Safe Operating Area




Maximum Drain Current vs Case Temperature






Typical Characteristics(Cont.)


Typical Transfer Characteristics




Single Pulse Maximum Power Dissipation




Transient Thermal Response Curves



Reel Dimension




Carrier Tape Dimension



Recommended wave soldering condition

Product	Peak Temperature	Soldering Time
Pb-free devices	260 +0/-5 °C	5 +1/-1 seconds


Recommended temperature profile for IR reflow



Profile feature	Sn-Pb eutectic Assembly	Pb-free Assembly
Average ramp-up rate (T _{smax} to T _p)	3°C/second max.	3°C/second max.
Preheat		
-Temperature Min(T _{s min})	100°C	150°C
-Temperature Max(T _{s max})	150°C	200°C
-Time(t _{s min} to t _{s max})	60-120 seconds	60-180 seconds
Time maintained above:		
-Temperature (T _L)	183°C	217°C
- Time (t _L)	60-150 seconds	60-150 seconds
Peak Temperature(T _P)	240 +0/-5 °C	260 +0/-5 °C
Time within 5°C of actual peak temperature(tp)	10-30 seconds	20-40 seconds
Ramp down rate	6°C/second max.	6°C/second max.
Time 25 °C to peak temperature	6 minutes max.	8 minutes max.


Note : All temperatures refer to topside of the package, measured on the package body surface.

TO-263 Dimension



The diagram shows three views of the TO-263 package: a top view with dimensions D, B, E, L, L3, b2, b, e, e1, L1, and L; a side view with dimensions A, c2, A1, c, L2, L4, and a gauge plane; and a bottom view with dimensions V and D1.

Marking :



Device Code → B015
 Date Code → P10
 □□□□

1 2 3

Style : Pin 1.Gate 2.Drain
 3.Source

3-Lead Plastic Surface Mounted Package
CYStek Package Code : F3

Date Code : (From left to right)
 First Code : Year code, the last digit of Christian year. For example, 2014→4, 2015→, 2016→6, ..., etc.
 Second Code : Month code, Jan→A, Feb→B, Mar→C, Apr→D, May→E, Jun→F, Jul→G, Aug→H, Sep→J,
 Oct→K, Nov→L, Dec→M
 Third and fourth codes : production serial number, 01~99

DIM	Millimeters		Inches		DIM	Millimeters		Inches	
	Min.	Max.	Min.	Max.		Min.	Max.	Min.	Max.
A	4.470	4.670	0.176	0.184	e	2.540	TYP	0.100	TYP
A1	0.000	0.150	0.000	0.006	e1	4.980	5.180	0.196	0.204
B	1.120	1.420	0.044	0.056	L	14.940	15.500	0.588	0.610
b	0.710	0.910	0.028	0.036	L1	4.950	5.450	0.195	0.215
b1	1.170	1.370	0.046	0.054	L2	2.340	2.740	0.092	0.108
c	0.381	0.530	0.015	0.021	L3	1.300	1.700	0.051	0.067
c1	1.170	1.370	0.046	0.054	L4	0.250 BSC		0.010 BSC	
D	10.010	10.310	0.394	0.406	Φ	0°	8°	0°	8°
D1	7.562	8.562	0.245	0.337	V	5.880	6.880	0.231	0.271
E	8.500	8.900	0.335	0.350					

Notes : 1.Controlling dimension : millimeters.
 2.Maximum lead thickness includes lead finish thickness, and minimum lead thickness is the minimum thickness of base material.
 3.If there is any question with packing specification or packing method, please contact your local CYStek sales office.

Material :

- Lead : Pure tin plated.
- Mold Compound : Epoxy resin family, flammability solid burning class:UL94V-0.

Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of CYStek.
- CYStek reserves the right to make changes to its products without notice.
- CYStek **semiconductor products are not warranted to be suitable for use in Life-Support Applications, or systems.**
- CYStek assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.