

**P-Channel Enhancement Mode Power MOSFET**


# MTD010P03J3

<b>BV<sub>DSS</sub></b>	<b>-30V</b>
<b>I<sub>D</sub>@V<sub>GS</sub>=-10V, T<sub>C</sub>=25°C</b>	<b>-43A</b>
<b>I<sub>D</sub>@V<sub>GS</sub>=-10V, T<sub>A</sub>=25°C</b>	<b>-9.3A</b>
<b>R<sub>DS(ON)</sub>@V<sub>GS</sub>=-10V, I<sub>D</sub>=-20A</b>	<b>11.3mΩ (typ)</b>
<b>R<sub>DS(ON)</sub>@V<sub>GS</sub>=-5V, I<sub>D</sub>=-15A</b>	<b>16.7mΩ (typ)</b>


**Features**

- Low On Resistance
- Simple Drive Requirement
- Low Gate Charge
- Fast Switching Characteristic
- Pb-free lead plating and halogen-free package

**Symbol**




**Outline**



**Ordering Information**

Device	Package	Shipping
MTD010P03J3-0-T3-G	TO-252 (Pb-free lead plating and halogen-free package)	2500 pcs / Tape & Reel



**Absolute Maximum Ratings** ( $T_C=25^{\circ}\text{C}$ )

Parameter	Symbol	Limits	Unit
Drain-Source Voltage (Note 1)	$V_{DS}$	-30	V
Gate-Source Voltage	$V_{GS}$	$\pm 20$	
Continuous Drain Current @ $T_C=25^{\circ}\text{C}$ , $V_{GS}=-10\text{V}$ (Note 1)	$I_D$	-43	A
Continuous Drain Current @ $T_C=100^{\circ}\text{C}$ , $V_{GS}=-10\text{V}$ (Note 1)		-30.4	
Continuous Drain Current @ $T_A=25^{\circ}\text{C}$ , $V_{GS}=-10\text{V}$ (Note 4)	$I_{DSM}$	-9.3	
Continuous Drain Current @ $T_A=70^{\circ}\text{C}$ , $V_{GS}=-10\text{V}$ (Note 4)		-7.4	
Pulsed Drain Current @ $V_{GS}=-10\text{V}$ (Note 3)	$I_{DM}$	-172	
Avalanche Current @ $L=100\mu\text{H}$ (Note 5)	$I_{AS}$	-43	
Single Pulse Avalanche Energy @ $L=1\text{mH}$ , $I_D=-20\text{Amps}$ , $V_{DD}=-25\text{V}$ (Note 5)	$E_{AS}$	200	mJ
Power Dissipation	$P_D$	$T_C=25^{\circ}\text{C}$ (Note 1)	54
		$T_C=100^{\circ}\text{C}$ (Note 1)	27
	$P_{DSM}$	$T_A=25^{\circ}\text{C}$ (Note 2)	2.5
		$T_A=70^{\circ}\text{C}$ (Note 2)	1.6
Operating Junction and Storage Temperature	$T_j, T_{stg}$	-55~+175	$^{\circ}\text{C/W}$

\*Drain current limited by maximum junction temperature

**Thermal Data**

Parameter	Symbol	Value	Unit
Thermal Resistance, Junction-to-case, max	$R_{\theta JC}$	2.8	$^{\circ}\text{C/W}$
Thermal Resistance, Junction-to-ambient, max (Note2)	$R_{\theta JA}$	50	
Thermal Resistance, Junction-to-ambient, max (Note4)		110	

Note : 1. The power dissipation  $P_D$  is based on  $T_{J(MAX)}=175^{\circ}\text{C}$ , using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used.

2. The value of  $R_{\theta JA}$  is measured with the device mounted on 1 in<sup>2</sup> FR-4 board with 2 oz. copper, in a still air environment with  $T_A=25^{\circ}\text{C}$ . The power dissipation  $P_{DSM}$  is based on  $R_{\theta JA}$  and the maximum allowed junction temperature of  $150^{\circ}\text{C}$ . The value in any given application depends on the user's specific board design.

3. Pulse width limited by junction temperature  $T_{J(MAX)}=175^{\circ}\text{C}$ . Ratings are based on low frequency and low duty cycles to keep initial  $T_J=25^{\circ}\text{C}$ .


4. When mounted on the minimum pad size recommended (PCB mount),  $t \leq 10\text{s}$ .

5. 100% tested by condition of  $V_{DD}=-15\text{V}$ ,  $I_D=-30\text{A}$ ,  $L=0.1\text{mH}$ ,  $V_{GS}=-10\text{V}$ .

**Characteristics (Tj=25°C, unless otherwise specified)**

Symbol	Min.	Typ.	Max.	Unit	Test Conditions
<b>Static</b>					
BV <sub>DSS</sub>	-30	-	-	V	V <sub>GS</sub> =0V, I <sub>D</sub> =-250μA
ΔBV <sub>DSS</sub> /ΔT <sub>j</sub>	-	-14	-	mV/°C	Reference to 25°C, I <sub>D</sub> =2-50μA
V <sub>GS(th)</sub>	-1.7	-	-2.8	V	V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> =-250μA
*G <sub>FS</sub>	-	14.8	-	S	V <sub>DS</sub> = -10V, I <sub>D</sub> =-10A
I <sub>GSS</sub>	-	-	±100	nA	V <sub>GS</sub> =±20V, V <sub>DS</sub> =0V
I <sub>DSS</sub>	-	-	-1	μA	V <sub>DS</sub> = -30V, V <sub>GS</sub> = 0V
	-	-	-5		V <sub>DS</sub> = -30V, V <sub>GS</sub> = 0V, T <sub>j</sub> =55°C
*R <sub>DS(ON)</sub>	-	11.3	15	mΩ	V <sub>GS</sub> = -10V, I <sub>D</sub> =-20A
	-	16.7	23		V <sub>GS</sub> = -5V, I <sub>D</sub> =-15A
<b>Dynamic</b>					
*Q <sub>g</sub>	36	45	54	nC	V <sub>DS</sub> =-15V, V <sub>GS</sub> =-10V, I <sub>D</sub> =-12A
*Q <sub>gs</sub>	-	8.6	-		
*Q <sub>gd</sub>	-	8.5	-		
*t <sub>d(ON)</sub>	-	13.6	-	ns	V <sub>DD</sub> =-15V, I <sub>D</sub> =-12A, V <sub>GS</sub> =-10V, R <sub>G</sub> =1Ω
*t <sub>r</sub>	-	20	-		
*t <sub>d(OFF)</sub>	-	76.6	-		
*t <sub>f</sub>	-	17.4	-		
C <sub>iss</sub>	-	2436	3166	pF	V <sub>GS</sub> =0V, V <sub>DS</sub> =-15V, f=1MHz
C <sub>oss</sub>	-	233	-		
C <sub>rss</sub>	-	158	-		
R <sub>g</sub>	-	9.1	-		
<b>Source-Drain Diode</b>					
*I <sub>S</sub>	-	-	-43	A	
*I <sub>SM</sub>	-	-	-172		
*V <sub>SD</sub>	-	-0.73	-1	V	I <sub>S</sub> =-1A, V <sub>GS</sub> =0V
*t <sub>rr</sub>	-	15.5	20	ns	V <sub>GS</sub> =0V, I <sub>F</sub> =-1A, dI <sub>F</sub> /dt=100A/μs
*Q <sub>rr</sub>	-	8.1	-	nC	


\*Pulse Test : Pulse Width ≤300μs, Duty Cycle≤2%

**Recommended soldering footprint**

 Unit (  $\frac{\text{mm}}{\text{inch}}$  )




**Typical Characteristics**


Typical Output Characteristics




Brekdown Voltage vs Ambient Temperature




Static Drain-Source On-State resistance vs Drain Current




Source Drain Current vs Source-Drain Voltage



Static Drain-Source On-State Resistance vs Gate-Source Voltage




Drain-Source On-State Resistance vs Junction Temperature




## Typical Characteristics(Cont.)


Capacitance vs Drain-to-Source Voltage




Threshold Voltage vs Junction Temperature




Forward Transfer Admittance vs Drain Current




Gate Charge Characteristics



Maximum Safe Operating Area




Maximum Drain Current vs Junction Temperature






**Typical Characteristics(Cont.)**


Typical Transfer Characteristics



Single Pulse Power Rating, Junction to Ambient  
 (Note on page 2)



Transient Thermal Response Curves






**Recommended wave soldering condition**

Product	Peak Temperature	Soldering Time
Pb-free devices	260 +0/-5 °C	5 +1/-1 seconds

**Recommended temperature profile for IR reflow**




Profile feature	Sn-Pb eutectic Assembly	Pb-free Assembly
Average ramp-up rate (T <sub>smax</sub> to T <sub>p</sub> )	3°C/second max.	3°C/second max.
Preheat		
-Temperature Min(T <sub>s min</sub> )	100°C	150°C
-Temperature Max(T <sub>s max</sub> )	150°C	200°C
-Time(t <sub>s min</sub> to t <sub>s max</sub> )	60-120 seconds	60-180 seconds
Time maintained above:		
-Temperature (T <sub>L</sub> )	183°C	217°C
- Time (t <sub>L</sub> )	60-150 seconds	60-150 seconds
Peak Temperature(T <sub>p</sub> )	240 +0/-5 °C	260 +0/-5 °C
Time within 5°C of actual peak temperature(tp)	10-30 seconds	20-40 seconds
Ramp down rate	6°C/second max.	6°C/second max.
Time 25 °C to peak temperature	6 minutes max.	8 minutes max.

Note : All temperatures refer to topside of the package, measured on the package body surface.



**TO-252 Dimension**



3-Lead TO-252 Plastic Surface Mount Package  
 CYStek Package Code: J3

Style: Pin 1.Gate 2.Drain 3.Source 4.Drain

DIM	Inches		Millimeters		DIM	Inches		Millimeters	
	Min.	Max.	Min.	Max.		Min.	Max.	Min.	Max.
A	0.087	0.094	2.200	2.400	e	0.086	0.094	2.186	2.386
A1	0.000	0.005	0.000	0.127	e1	0.172	0.188	4.372	4.772
B	0.039	0.048	0.990	1.210	H	0.163	REF	4.140	REF
b	0.026	0.034	0.660	0.860	K	0.190	REF	4.830	REF
b1	0.026	0.034	0.660	0.860	L	0.386	0.409	9.800	10.400
C	0.018	0.023	0.460	0.580	L1	0.114	REF	2.900	REF
C1	0.018	0.023	0.460	0.580	L2	0.055	0.067	1.400	1.700
D	0.256	0.264	6.500	6.700	L3	0.024	0.039	0.600	1.000
D1	0.201	0.215	5.100	5.460	P	0.026	REF	0.650	REF
E	0.236	0.244	6.000	6.200	V	0.211	REF	5.350	REF

Notes: 1.Controlling dimension: millimeters.  
 2.Maximum lead thickness includes lead finish thickness, and minimum lead thickness is the minimum thickness of base material.  
 3.If there is any question with packing specification or packing method, please contact your local CYStek sales office.

**Material:**

- Lead : Pure tin plated.
- Mold Compound: Epoxy resin family, flammability solid burning class: UL94V-0.

**Important Notice:**

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of CYStek.
- CYStek reserves the right to make changes to its products without notice.
- CYStek **semiconductor products are not warranted to be suitable for use in Life-Support Applications, or systems.**
- CYStek assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.