

N-CHANNEL MOSFET (dual transistors)


MTDN1034C6

Features


- High speed switching
- Low-voltage drive(1.5V)
- Easily designed drive circuits
- Easy to use in parallel
- Pb-free package

BV _{DSS}		30V
I _D @V _{GS} =4.5V, T _A =25°C		0.3A
R _{DS(on)(TYP)}	V _{GS} =4.5V, I _D =200mA	0.85 Ω
	V _{GS} =2.5V, I _D =175mA	1.23 Ω
	V _{GS} =1.8V, I _D =150mA	1.8 Ω
	V _{GS} =1.5V, I _D =40mA	2.3 Ω

Equivalent Circuit




Outline



Ordering Information

Device	Package	Shipping
MTDN1034C6-0-T1-G	SOT-563 (Pb-free lead plating and halogen-free package)	3000 pcs / tape & reel





The following characteristics apply to both Tr1 and Tr2

Absolute Maximum Ratings (Ta=25°C, unless otherwise specified)

Parameter	Symbol	Limits	Unit
Drain-Source Voltage	V _{DSS}	30	V
Gate-Source Voltage	V _{GSS}	±8	
Continuous Drain Current @ V _{GS} =4.5V, T _A =25°C	I _D	0.3	A
Continuous Drain Current @ V _{GS} =4.5V, T _A =85°C		0.22	
Pulsed Drain Current	I _{DM}	1.6 (Note 1)	
Power Dissipation	P _d	150 (Note 2)	mW
Operating Junction Temperature Range	T _j	-55~+150	°C
Storage Temperature Range	T _{stg}	-55~+150	

Note : 1. Pulse test, pulse width≤300μs, duty≤2%
 2. 120mW per element must not be exceeded.

Electrical Characteristics (Ta=25°C, unless otherwise specified)


Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Static					
BV _{DSS} *	30	-	-	V	V _{GS} =0V, I _D =10μA
V _{GS(th)}	0.5	0.78	1.1		V _{DS} =V _{GS} , I _D =250μA
I _{GSS}	-	-	±1	μA	V _{GS} =±8V, V _{DS} =0V
I _{DSS}	-	-	100	nA	V _{DS} =30V, V _{GS} =0V
R _{DS(ON)} *	-	0.85	1.5	Ω	V _{GS} =4.5V, I _D =200mA
	-	1.23	3		V _{GS} =2.5V, I _D =175mA
	-	1.8	4		V _{GS} =1.8V, I _D =150mA
	-	2.3	5		V _{GS} =1.5V, I _D =40mA
G _{FS}	-	460	-	mS	V _{DS} =10V, I _D =200mA
Dynamic					
C _{iss}	-	33.5	-	pF	V _{DS} =15V, V _{GS} =0V, f=1MHz
C _{oss}	-	6.1	-		
C _{rss}	-	2.5	-		
Q _g	-	495	-	pC	V _{DS} =15V, I _D =300mA, V _{GS} =4.5V
Q _{gs}	-	49	-		
Q _{gd}	-	175	-		
t _{d(on)}	-	-	50	ns	V _{DD} =15V, I _D =200mA, V _{GS} =4.5V, R _G =10Ω
t _r	-	-	25		
t _{d(off)}	-	-	50		
t _f	-	-	25		
Source-Drain Diode					
I _S	-	-	0.3	A	
I _{SM}	-	-	2		
V _{SD}	-	0.81	1	V	I _S =150mA, V _{GS} =0V

*Pulse Test : Pulse Width ≤300μs, Duty Cycle ≤2%




Typical Characteristics


Typical Output Characteristics




Breakdown Voltage vs Ambient Temperature




Static Drain-Source On-State resistance vs Drain Current




Reverse Drain Current vs Source-Drain Voltage



Static Drain-Source On-State Resistance vs Gate-Source Voltage




Drain-Source On-State Resistance vs Junction Temperature






Typical Characteristics(Cont.)


Capacitance vs Drain-to-Source Voltage




Threshold Voltage vs Junction Temperature




Single Pulse Power Rating, Junction to Ambient
 (Note on page 2)




Gate Charge Characteristics



Maximum Safe Operating Area




Maximum Drain Current vs Junction Temperature






Typical Characteristics(Cont.)


Typical Transfer Characteristics




Forward Transfer Admittance vs Drain Current




Transient Thermal Response Curves



Reel Dimension




Carrier Tape Dimension



Recommended wave soldering condition

Product	Peak Temperature	Soldering Time
Pb-free devices	260 +0/-5 °C	5 +1/-1 seconds


Recommended temperature profile for IR reflow



Profile feature	Sn-Pb eutectic Assembly	Pb-free Assembly
Average ramp-up rate (T _{smax} to T _p)	3°C/second max.	3°C/second max.
Preheat		
-Temperature Min(T _{s min})	100°C	150°C
-Temperature Max(T _{s max})	150°C	200°C
-Time(t _{s min} to t _{s max})	60-120 seconds	60-180 seconds
Time maintained above:		
-Temperature (T _L)	183°C	217°C
- Time (t _L)	60-150 seconds	60-150 seconds
Peak Temperature(T _P)	240 +0/-5 °C	260 +0/-5 °C
Time within 5°C of actual peak temperature(tp)	10-30 seconds	20-40 seconds
Ramp down rate	6°C/second max.	6°C/second max.
Time 25 °C to peak temperature	6 minutes max.	8 minutes max.

Note : All temperatures refer to topside of the package, measured on the package body surface.

SOT-563 Dimension



DIM	Inches		Millimeters		DIM	Inches		Millimeters	
	Min.	Max.	Min.	Max.		Min.	Max.	Min.	Max.
A	0.021	0.024	0.525	0.600	b	0.007	0.011	0.170	0.270
A1	0.000	0.002	0.000	0.050	E1	0.043	0.051	1.100	1.300
e	0.018	0.022	0.450	0.550	E	0.059	0.067	1.500	1.700
c	0.004	0.006	0.090	0.160	L	0.004	0.012	0.100	0.300
D	0.059	0.067	1.500	1.700	θ	7° REF		7° REF	

Notes : 1.Controlling dimension : millimeters.
 2.Maximum lead thickness includes lead finish thickness, and minimum lead thickness is the minimum thickness of base material.
 3.If there is any question with packing specification or packing method, please contact your local CYStek sales office.

Material :

- Lead : Pure tin plated.
- Mold Compound : Epoxy resin family, flammability solid burning class:UL94V-0.

Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of CYStek.
- CYStek reserves the right to make changes to its products without notice.
- CYStek **semiconductor products are not warranted to be suitable for use in Life-Support Applications, or systems.**
- CYStek assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.