

N-Channel Enhancement Mode Power MOSFET


MTB014N03N3

Features


- Low On Resistance
- Low Gate Charge
- Fast Switching Characteristic

BV_{DSS}	30V
$I_D @ V_{GS}=10V, T_A=25^\circ C$	5.5A
$R_{DS(ON) typ. @ V_{GS}=10V, I_D=5A}$	14mΩ
$R_{DS(ON) typ. @ V_{GS}=4.5V, I_D=4A}$	17mΩ

Equivalent Circuit




Outline



Ordering Information

Device	Package	Shipping
MTB014N03N3-0-T1-G	SOT-23 (Pb-free lead plating and halogen-free package)	3000 pcs / Tape & Reel



**Absolute Maximum Ratings (T_A=25°C)**

Parameter	Symbol	Limits	Unit	
Drain-Source Voltage	V _{DS}	30	V	
Gate-Source Voltage	V _{GS}	±20		
Continuous Drain Current @ V _{GS} =10V, T _A =25°C	I _D	5.5	A	
Continuous Drain Current @ V _{GS} =10V, T _A =70°C		4.4		
Pulsed Drain Current	I _{DM}	22		
Continuous Body Diode Forward Current @ T _A =25°C	I _S	0.9		
Avalanche Current @ L=0.1mH	I _{AS}	15		
Avalanche Energy @ L=0.5mH	E _{AS}	16		mJ
Total Power Dissipation	P _D	T _A =25°C	1.1	W
		T _A =70°C	0.7	
Operating Junction and Storage Temperature Range	T _J , T _{stg}	-55~+150	°C	

Thermal Data

Parameter	Symbol	Steady State	Unit
Thermal Resistance, Junction-to-ambient	R _{θJA}	112	°C/W

Note:

- *a. The value of R_{θJA} is measured with the device mounted on 1 in² FR-4 board with 2 oz. copper, in a still air environment with T_A=25°C. The power dissipation P_D is based on R_{θJA} and the maximum allowed junction temperature of 150°C. The value in any given application depends on the user's specific board design.
- *b. Repetitive rating, pulse width limited by junction temperature T_{J(MAX)}=150°C. Ratings are based on low frequency and low duty cycles to keep initial T_J=25°C.



Electrical Characteristics (T_A=25°C, unless otherwise specified)

Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Static					
BV _{DSS}	30	-	-	V	V _{GS} =0V, I _D =250μA
V _{GS(th)}	1	-	2.5		V _{DS} =V _{GS} , I _D =250μA
G _{FS}	-	6.3	-	S	V _{DS} =10V, I _D =3A
I _{GSS}	-	-	±100	nA	V _{GS} =±20V, V _{DS} =0V
I _{DSS}	-	-	1	μA	V _{DS} =24V, V _{GS} =0V
R _{DS(ON)}	-	14	18	mΩ	V _{GS} =10V, I _D =5A
	-	17	24		V _{GS} =4.5V, I _D =4A
Dynamic					
C _{iss}	-	850	-	pF	V _{DS} =15V, V _{GS} =0V, f=1MHz
C _{oss}	-	120	-		
C _{rss}	-	95	-		
R _g	-	3	-	Ω	f=1MHz
Q _g *1, 2	-	18	-	nC	V _{DS} =15V, I _D =5A, V _{GS} =10V
Q _{gs} *1, 2	-	2.6	-		
Q _{gd} *1, 2	-	3.6	-		
t _{d(ON)} *1, 2	-	9	-	ns	V _{DS} =15V, I _D =5A, V _{GS} =10V, R _{GS} =1Ω
t _r *1, 2	-	32	-		
t _{d(OFF)} *1, 2	-	37	-		
t _f *1, 2	-	7	-		
Source-Drain Diode					
V _{SD} *1	-	0.8	1.2	V	I _S =5A, V _{GS} =0V
t _{rr}	-	10	-	ns	I _F =5A, dI _F /dt=100A/μs
Q _{rr}	-	4.5	-	nC	


Note:

*1. Pulse Test : Pulse Width ≤300μs, Duty Cycle≤2%


*2. Independent of operating temperature

Typical Characteristics


Typical Output Characteristics




Breakdown Voltage vs Ambient Temperature




Static Drain-Source On-State resistance vs Drain Current




Body Diode Current vs Source-Drain Voltage



Static Drain-Source On-State Resistance vs Gate-Source Voltage




Drain-Source On-State Resistance vs Junction Temperature




Typical Characteristics (Cont.)


Capacitance vs Drain-to-Source Voltage




Threshold Voltage vs Junction Temperature




Forward Transfer Admittance vs Drain Current




Gate Charge Characteristics



Maximum Safe Operating Area




Maximum Drain Current vs Junction Temperature




Typical Characteristics (Cont.)


Single Pulse Power Rating, Junction to Ambient



Transient Thermal Response Curves




Recommended soldering footprint




Unit : mm

Reel Dimension




Carrier Tape Dimension



Recommended wave soldering condition

Product	Peak Temperature	Soldering Time
Pb-free devices	260 +0/-5 °C	5 +1/-1 seconds


Recommended temperature profile for IR reflow



Profile feature	Sn-Pb eutectic Assembly	Pb-free Assembly
Average ramp-up rate (T _{smax} to T _p)	3°C/second max.	3°C/second max.
Preheat		
-Temperature Min(T _{s min})	100°C	150°C
-Temperature Max(T _{s max})	150°C	200°C
-Time(t _{s min} to t _{s max})	60-120 seconds	60-180 seconds
Time maintained above:		
-Temperature (T _L)	183°C	217°C
- Time (t _L)	60-150 seconds	60-150 seconds
Peak Temperature(T _P)	240 +0/-5 °C	260 +0/-5 °C
Time within 5°C of actual peak temperature(t _p)	10-30 seconds	20-40 seconds
Ramp down rate	6°C/second max.	6°C/second max.
Time 25 °C to peak temperature	6 minutes max.	8 minutes max.

Note : All temperatures refer to topside of the package, measured on the package body surface.

SOT-23 Dimension



The diagram shows three views of the SOT-23 package: a top view with dimensions D, b, E, E1, e, and e1; a side view with dimensions L, L1, c, and θ ; and a bottom view with dimensions A1, A2, and A. A marking diagram shows the layout on the package with 'BTNT' in the center, 'Date Code' at the top, 'Device Code' on the left, and pins 'G' and 'S' at the bottom. A note specifies the style: Pin 1.Gate 2.Source 3.Drain.

Marking:

Style: Pin 1.Gate 2.Source 3.Drain

3-Lead SOT-23 Plastic Surface Mounted Package
 CYStek Package Code: N3

Date Code: Year+Month
 Year: 3→2003, 4→2004
 Month: 1→1, 2→2, . . .
 9→9, A→10, B→11, C→12

DIM	Inches		Millimeters		DIM	Inches		Millimeters	
	Min.	Max.	Min.	Max.		Min.	Max.	Min.	Max.
A	0.041	0.049	1.05	1.25	E	0.104	0.116	2.65	2.95
A1	0.000	0.004	0.00	0.10	e	0.037 BSC		0.95 BSC	
A2	0.041	0.045	1.05	1.15	e1	0.071	0.079	1.80	2.00
b	0.012	0.020	0.30	0.50	L	0.012	0.024	0.30	0.60
c	0.004	0.008	0.10	0.20	L1	0.024 REF		0.60 REF	
D	0.111	0.119	2.82	3.02	θ	0°	8°	0°	8°
E1	0.059	0.067	1.50	1.70					

Notes: 1.Controlling dimension: millimeters.

2.Maximum lead thickness includes lead finish thickness, and minimum lead thickness is the minimum thickness of base material.

3.If there is any question with packing specification or packing method, please contact your local CYStek sales office.

Material:

- Lead: Pure tin plated.
- Mold Compound: Epoxy resin family, flammability solid burning class: UL94V-0.

Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of CYStek.
- CYStek reserves the right to make changes to its products without notice.
- CYStek **semiconductor products are not warranted to be suitable for use in Life-Support Applications, or systems.**
- CYStek assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.