

P-Channel Enhancement Mode MOSFET


MTB040P04J3

Features


- Low On Resistance
- Low Gate Charge
- Fast Switching Characteristic

BV_{DSS}	-40V
$I_D@V_{GS}=-10V, T_C=25^{\circ}C$	-20A
$I_D@V_{GS}=-10V, T_A=25^{\circ}C$	-6.5A
$R_{DS(ON) typ.}@V_{GS}=-10V, I_D=-6A$	33mΩ
$R_{DS(ON) typ.}@V_{GS}=-4.5V, I_D=-5A$	48mΩ

Equivalent Circuit




Outline



Ordering Information

Device	Package	Shipping
MTB040P04J3-0-T3-G	TO-252 (Pb-free lead plating and halogen-free package)	2500 pcs / Tape & Reel





Absolute Maximum Ratings (TA=25°C)

Parameter	Symbol	Limits	Unit	
Drain-Source Voltage	V _{DS}	-40	V	
Gate-Source Voltage	V _{GS}	±20		
Continuous Drain Current @ V _{GS} =-10V, T _C =25°C	I _D	-20	A	
Continuous Drain Current @ V _{GS} =-10V, T _C =100°C		-13		
Continuous Drain Current @ V _{GS} =-10V, T _A =25°C		-6.5		
Continuous Drain Current @ V _{GS} =-10V, T _A =70°C		-5.2		
Pulsed Drain Current	I _{DM}	-60		
Continuous Body Diode Forward Current @ T _C =25°C	I _S	-20		
Avalanche Current @ L=0.1mH	I _{AS}	-15		
Avalanche Energy @ L=0.5mH	E _{AS}	16	mJ	
Total Power Dissipation	P _D	T _C =25°C	33	W
		T _C =100°C	13	
		T _A =25°C	3.3	
		T _A =70°C	2.1	
Operating Junction and Storage Temperature Range	T _J , T _{stg}	-55~+150	°C	

Thermal Data

Parameter	Symbol	Steady State	Unit
Thermal Resistance, Junction-to-case	R _{θJC}	3.8	°C/W
Thermal Resistance, Junction-to-ambient	R _{θJA}	38	

Note:

- *a. The power dissipation P_D is based on T_{J(MAX)}=150°C, using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used.
- *b. The value of R_{θJA} is measured with the device mounted on 1 in² FR-4 board with 2 oz. copper, in a still air environment with T_A=25°C. The power dissipation P_D is based on R_{θJA} and the maximum allowed junction temperature of 150°C. The value in any given application depends on the user's specific board design.
- *c. Repetitive rating, pulse width limited by junction temperature T_{J(MAX)}=150°C. Ratings are based on low frequency and low duty cycles to keep initial T_J=25°C.



Electrical Characteristics (T_A=25°C, unless otherwise specified)

Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Static					
BV _{DSS}	-40	-	-	V	V _{GS} =0V, I _D =-250μA
V _{GS(th)}	-1	-	-2.5		V _{DS} =V _{GS} , I _D =-250μA
G _{FS}	-	8.6	-	S	V _{DS} =-10V, I _D =-5A
I _{GSS}	-	-	±100	nA	V _{GS} =±20V, V _{DS} =0V
I _{DSS}	-	-	-1	μA	V _{DS} =-32V, V _{GS} =0V
R _{DS(ON)}	-	33	43	mΩ	V _{GS} =-10V, I _D =-6A
	-	48	67		V _{GS} =-4.5V, I _D =-5A
Dynamic					
C _{iss}	-	930	-	pF	V _{DS} =-20V, V _{GS} =0V, f=1MHz
C _{oss}	-	80	-		
C _{rss}	-	60	-		
R _g	-	22	-	Ω	f=1MHz
Q _g *1, 2	-	19	-	nC	V _{DS} =-20V, I _D =-6A, V _{GS} =-10V
Q _{gs} *1, 2	-	2.8	-		
Q _{gd} *1, 2	-	3.5	-		
t _{d(ON)} *1, 2	-	6.8	-	ns	V _{DS} =-20V, I _D =-6A, V _{GS} =-10V, R _{GS} =1Ω
t _r *1, 2	-	19	-		
t _{d(OFF)} *1, 2	-	66	-		
t _f *1, 2	-	32	-		
Source-Drain Diode					
V _{SD} *1	-	-0.85	-1.2	V	I _S =-6A, V _{GS} =0V
t _{rr}	-	9.6	-	ns	I _F =-6A, dI _F /dt=100A/μs
Q _{rr}	-	5	-	nC	

Note:


*1. Pulse Test : Pulse Width ≤300μs, Duty Cycle≤2%

*2. Independent of operating temperature




Typical Characteristics


Typical Output Characteristics




Breakdown Voltage vs Ambient Temperature




Static Drain-Source On-State resistance vs Drain Current




Body Diode Current vs Source-Drain Voltage



Static Drain-Source On-State Resistance vs Gate-Source Voltage




Drain-Source On-State Resistance vs Junction Temperature




Typical Characteristics (Cont.)


Capacitance vs Drain-to-Source Voltage




Threshold Voltage vs Junction Temperature




Forward Transfer Admittance vs Drain Current




Gate Charge Characteristics



Maximum Safe Operating Area




Maximum Drain Current vs Junction Temperature




Typical Characteristics (Cont.)


Single Pulse Power Rating, Junction to Ambient




Transient Thermal Response Curves




Recommended Soldering Footprint & Stencil Design



Reel Dimension




Carrier Tape Dimension



Recommended wave soldering condition

Product	Peak Temperature	Soldering Time
Pb-free devices	260 +0/-5 °C	5 +1/-1 seconds


Recommended temperature profile for IR reflow



Profile feature	Sn-Pb eutectic Assembly	Pb-free Assembly
Average ramp-up rate (T _{smax} to T _p)	3°C/second max.	3°C/second max.
Preheat		
-Temperature Min(T _{s min})	100°C	150°C
-Temperature Max(T _{s max})	150°C	200°C
-Time(t _{s min} to t _{s max})	60-120 seconds	60-180 seconds
Time maintained above:		
-Temperature (T _L)	183°C	217°C
- Time (t _L)	60-150 seconds	60-150 seconds
Peak Temperature(T _P)	240 +0/-5 °C	260 +0/-5 °C
Time within 5°C of actual peak temperature(tp)	10-30 seconds	20-40 seconds
Ramp down rate	6°C/second max.	6°C/second max.
Time 25 °C to peak temperature	6 minutes max.	8 minutes max.

Note : All temperatures refer to topside of the package, measured on the package body surface.


TO-252 Dimension



3-Lead TO-252 Plastic Surface Mount Package
 CYStek Package Code: J3

Style: Pin 1.Gate 2.Drain 3.Source 4.Drain

Marking:



Device Code → B040
 Date Code → P04 H
 Assembly Site code :
 Blank → Site1
 H → Site2

Date Code(counting from left to right) :
 1st code: year code, the last digit of Christian year
 2nd code : month code, Jan→A, Feb→B, Mar→C,
 Apr→D, May→E, Jun→F, Jul→G, Aug→H,
 Sep→J, Oct→K, Nov→L, Dec→M
 3rd and 4th codes : production serial number, 01~99

DIM	Inches		Millimeters		DIM	Inches		Millimeters	
	Min.	Max.	Min.	Max.		Min.	Max.	Min.	Max.
A	0.087	0.093	2.200	2.380	e	0.090 BSC		2.286 BSC	
A1	0.000	0.007	0.000	0.200	H	0.370	0.413	9.400	10.500
A2	0.038	0.046	0.970	1.170	L	0.054	0.069	1.380	1.750
b	0.026	0.035	0.680	0.900	L1	0.114 REF		2.900 REF	
b3	0.204	0.214	5.200	5.460	L2	0.020 BSC		0.510 BSC	
c	0.017	0.024	0.430	0.610	L3	0.035	0.050	0.880	1.280
D	0.235	0.245	5.980	6.220	L4	0.019	0.039	0.500	1.000
D1	0.209 REF		5.300 REF		L5	0.065	0.077	1.650	1.950
E	0.252	0.264	6.400	6.730	θ	0°	8°	0°	8°
E1	0.182	-	4.630	-					

Notes: 1.Controlling dimension: millimeters.
 2.Maximum lead thickness includes lead finish thickness, and minimum lead thickness is the minimum thickness of base material.
 3.If there is any question with packing specification or packing method, please contact your local CYStek sales office.

Material:

- Lead : Pure tin plated.
- Mold Compound: Epoxy resin family, flammability solid burning class: UL94V-0.

Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of CYStek.
- CYStek reserves the right to make changes to its products without notice.
- CYStek **semiconductor products are not warranted to be suitable for use in Life-Support Applications, or systems.**
- CYStek assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.