

**N- AND P-Channel Enhancement Mode Power MOSFET**


# MTC6601DFA6

**Features**


- Simple drive requirement
- Low Gate Charge
- Fast switching speed

	N-CH	P-CH
$BV_{DSS}$	30V	-30V
$I_D@V_{GS}=(-)4.5V, T_C=25^\circ C$	5.7A	-4.2A
$I_D@V_{GS}=(-)4.5V, T_A=25^\circ C$	3.3A	-2.4A
$R_{DS(ON)typ.}@V_{GS}=(-)4.5V$	45mΩ	104mΩ
$R_{DS(ON)typ.}@V_{GS}=(-)2.5V$	60mΩ	133mΩ

**Equivalent Circuit**




**Outline**



**Ordering Information**

Device	Package	Shipping
MTC6601DFA6-0-T1-G	DFN2x2-6L (Pb-free lead plating and halogen-free package)	3000 pcs / Tape & Reel



**Absolute Maximum Ratings (TA=25°C)**

Parameter	Symbol	Limits		Unit	
		N-CH	P-CH		
Drain-Source Voltage	V <sub>DS</sub>	30	-30	V	
Gate-Source Voltage	V <sub>GS</sub>	±12	±12		
Continuous Drain Current @ V <sub>GS</sub> =(-)4.5V, T <sub>C</sub> =25°C	*a	I <sub>D</sub>	5.7	-4.2	A
Continuous Drain Current @ V <sub>GS</sub> =(-)4.5V, T <sub>C</sub> =100°C	*a		3.6	-2.7	
Continuous Drain Current @ V <sub>GS</sub> =(-)4.5V, T <sub>A</sub> =25°C	*b		3.3	-2.4	
Continuous Drain Current @ V <sub>GS</sub> =(-)4.5V, T <sub>A</sub> =70°C	*b		2.6	-1.9	
Pulsed Drain Current	*c	I <sub>DM</sub>	22.8	-16.8	
Continuous Body Diode Forward Current @ T <sub>C</sub> =25°C	*a	I <sub>S</sub>	3.2	-3.2	
Pulsed Body Diode Forward Current @ T <sub>C</sub> =25°C	*a	I <sub>SM</sub>	12.8	-12.8	
Avalanche Current @ L=0.1mH		I <sub>AS</sub>	7	-7	
Avalanche Energy @ L=0.5mH		E <sub>AS</sub>	4	4	mJ
Total Power Dissipation	T <sub>C</sub> =25°C	P <sub>D</sub>	3.9		W
	T <sub>C</sub> =100°C		1.6		
	T <sub>A</sub> =25°C		1.3		
	T <sub>A</sub> =70°C		0.8		
Operating Junction and Storage Temperature Range		T <sub>J</sub> , T <sub>stg</sub>	-55~+150		°C

**Thermal Data**

Parameter	Symbol	Steady State	Unit
Thermal Resistance, Junction-to-case	R <sub>θJC</sub>	32	°C/W
Thermal Resistance, Junction-to-ambient	*b R <sub>θJA</sub>	96	

Note:

- \*a. The power dissipation P<sub>D</sub> is based on T<sub>J(MAX)</sub>=150°C, using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used.
- \*b. The value of R<sub>θJA</sub> is measured with the device mounted on 1 in<sup>2</sup> FR-4 board with 2 oz. copper, in a still air environment with T<sub>A</sub>=25°C. The power dissipation P<sub>D</sub> is based on R<sub>θJA</sub> and the maximum allowed junction temperature of 150°C. The value in any given application depends on the user's specific board design.
- \*c. Repetitive rating, pulse width limited by junction temperature T<sub>J(MAX)</sub>=150°C. Ratings are based on low frequency and low duty cycles to keep initial T<sub>J</sub>=25°C.



**N-Channel Electrical Characteristics (T<sub>A</sub>=25°C, unless otherwise specified)**

Symbol	Min.	Typ.	Max.	Unit	Test Conditions
<b>Static</b>					
BV <sub>DSS</sub>	30	-	-	V	V <sub>GS</sub> =0V, I <sub>D</sub> =250μA
V <sub>GS(th)</sub>	0.5	-	1.5		V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =250μA
G <sub>FS</sub>	-	2	-	S	V <sub>DS</sub> =10V, I <sub>D</sub> =1A
I <sub>GSS</sub>	-	-	±100	nA	V <sub>GS</sub> =±12V, V <sub>DS</sub> =0V
I <sub>DSS</sub>	-	-	1	μA	V <sub>DS</sub> =24V, V <sub>GS</sub> =0V
R <sub>DS(ON)</sub>	-	45	65	mΩ	V <sub>GS</sub> =4.5V, I <sub>D</sub> =3A
	-	60	90		V <sub>GS</sub> =2.5V, I <sub>D</sub> =2A
<b>Dynamic</b>					
C <sub>iss</sub>	-	315	-	pF	V <sub>DS</sub> =15V, V <sub>GS</sub> =0V, f=1MHz
C <sub>oss</sub>	-	46	-		
C <sub>rss</sub>	-	33	-		
R <sub>g</sub>	-	2	-	Ω	f=1MHz
Q <sub>g</sub> *1, 2	-	4.5	-	nC	V <sub>DS</sub> =15V, I <sub>D</sub> =3A, V <sub>GS</sub> =4.5V
Q <sub>g</sub> *1, 2	-	10	-		
Q <sub>gs</sub> *1, 2	-	1.6	-		
Q <sub>gd</sub> *1, 2	-	0.8	-		
t <sub>d(ON)</sub> *1, 2	-	3.5	-	ns	V <sub>DS</sub> =15V, I <sub>D</sub> =3A, V <sub>GS</sub> =10V, R <sub>GS</sub> =6Ω
t <sub>r</sub> *1, 2	-	16	-		
t <sub>d(OFF)</sub> *1, 2	-	25	-		
t <sub>f</sub> *1, 2	-	4.2	-		
<b>Source-Drain Diode</b>					
V <sub>SD</sub> *1	-	0.8	1.2	V	I <sub>S</sub> =1A, V <sub>GS</sub> =0V
t <sub>rr</sub>	-	7.7	-	ns	I <sub>F</sub> =1A, dI <sub>F</sub> /dt=100A/μs
Q <sub>rr</sub>	-	3.3	-	nC	

Note:

- \*1. Pulse Test : Pulse Width ≤300μs, Duty Cycle≤2%
- \*2. Independent of operating temperature



**P-Channel Electrical Characteristics (T<sub>A</sub>=25°C, unless otherwise specified)**

Symbol	Min.	Typ.	Max.	Unit	Test Conditions
<b>Static</b>					
BV <sub>DSS</sub>	-30	-	-	V	V <sub>GS</sub> =0V, I <sub>D</sub> =-250μA
V <sub>GS(th)</sub>	-0.5	-	-1.5		V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =-250μA
G <sub>FS</sub>	-	2.2	-	S	V <sub>DS</sub> =-10V, I <sub>D</sub> =-1A
I <sub>GSS</sub>	-	-	±100	nA	V <sub>GS</sub> =±12V, V <sub>DS</sub> =0V
I <sub>DSS</sub>	-	-	-1	μA	V <sub>DS</sub> =-24V, V <sub>GS</sub> =0V
R <sub>DS(ON)</sub>	-	104	145	mΩ	V <sub>GS</sub> =-4.5V, I <sub>D</sub> =-2A
	-	133	200		V <sub>GS</sub> =-2.5V, I <sub>D</sub> =-1A
<b>Dynamic</b>					
C <sub>iss</sub>	-	475	-	pF	V <sub>DS</sub> =-15V, V <sub>GS</sub> =0V, f=1MHz
C <sub>oss</sub>	-	36	-		
C <sub>rss</sub>	-	36	-		
R <sub>g</sub>	-	15	-	Ω	f=1MHz
Q <sub>g</sub> *1, 2	-	6	-	nC	V <sub>DS</sub> =-15V, I <sub>D</sub> =-2A, V <sub>GS</sub> =-4.5V
Q <sub>g</sub> *1, 2	-	12.5	-		
Q <sub>gs</sub> *1, 2	-	1.1	-		
Q <sub>gd</sub> *1, 2	-	1.9	-		
t <sub>d(ON)</sub> *1, 2	-	4.4	-	ns	V <sub>DS</sub> =-15V, I <sub>D</sub> =-2A, V <sub>GS</sub> =-10V, R <sub>GS</sub> =6Ω
t <sub>r</sub> *1, 2	-	16	-		
t <sub>d(OFF)</sub> *1, 2	-	37	-		
t <sub>f</sub> *1, 2	-	5	-		
<b>Source-Drain Diode</b>					
V <sub>SD</sub> *1	-	-0.85	-1.2	V	I <sub>S</sub> =-1A, V <sub>GS</sub> =0V
t <sub>rr</sub>	-	7	-	ns	I <sub>F</sub> =-1A, dI <sub>F</sub> /dt=100A/μs
Q <sub>rr</sub>	-	3	-	nC	


Note:

- \*1. Pulse Test : Pulse Width ≤300μs, Duty Cycle≤2%
- \*2. Independent of operating temperature




**Typical Characteristics : Q1( N-channel )**


Typical Output Characteristics




Breakdown Voltage vs Ambient Temperature




Static Drain-Source On-State resistance vs Drain Current




Body Diode Current vs Source-Drain Voltage









Static Drain-Source On-State Resistance vs Gate-Source Voltage



Drain-Source On-State Resistance vs Junction Temperature




## Typical Characteristics (Cont.) : Q1( N-channel)




**Typical Characteristics (Cont.) : Q1( N-channel)**

Single Pulse Power Rating, Junction to Ambient




Transient Thermal Response Curves




**Typical Characteristics : Q2( P-channel)**


Typical Output Characteristics




Breakdown Voltage vs Ambient Temperature




Static Drain-Source On-State resistance vs Drain Current




Body Diode Current vs Source-Drain Voltage



Static Drain-Source On-State Resistance vs Gate-Source Voltage




Drain-Source On-State Resistance vs Junction Temperature






**Typical Characteristics (Cont.) : Q2(P-channel)**


Capacitance vs Drain-to-Source Voltage




Threshold Voltage vs Junction Temperature




Forward Transfer Admittance vs Drain Current




Gate Charge Characteristics



Maximum Safe Operating Area




Maximum Drain Current vs Junction Temperature




**Typical Characteristics (Cont.) : Q2(P-channel)**


Single Pulse Power Rating, Junction to Ambient



Transient Thermal Response Curves




**Recommended Soldering Footprint**




Unit : mm

**Reel Dimension**




**Carrier Tape Dimension**



**Recommended wave soldering condition**

Product	Peak Temperature	Soldering Time
Pb-free devices	260 +0/-5 °C	5 +1/-1 seconds


**Recommended temperature profile for IR reflow**



Profile feature	Sn-Pb eutectic Assembly	Pb-free Assembly
Average ramp-up rate (Tsmax to Tp)	3°C/second max.	3°C/second max.
Preheat		
-Temperature Min(Ts min)	100°C	150°C
-Temperature Max(Ts max)	150°C	200°C
-Time(ts min to ts max)	60-120 seconds	60-180 seconds
Time maintained above:		
-Temperature (TL)	183°C	217°C
- Time (tL)	60-150 seconds	60-150 seconds
Peak Temperature(TP)	240 +0/-5 °C	260 +0/-5 °C
Time within 5°C of actual peak temperature(tp)	10-30 seconds	20-40 seconds
Ramp down rate	6°C/second max.	6°C/second max.
Time 25 °C to peak temperature	6 minutes max.	8 minutes max.

Note : All temperatures refer to topside of the package, measured on the package body surface.

**DFN2x2-6L Dimension**



DIM	Millimeters		Inches		DIM	Millimeters		Inches	
	Min.	Max.	Min.	Max.		Min.	Max.	Min.	Max.
A	0.700	0.800	0.028	0.031	E1	0.520	0.720	0.020	0.028
A1	0.000	0.050	0.000	0.002	b	0.250	0.350	0.010	0.014
A3	0.203 REF.		0.008 REF.		e	0.650 TYP.		0.026 TYP.	
D	1.900	2.100	0.075	0.083	k	0.250 REF.		0.010 REF.	
E	1.900	2.100	0.075	0.083	k1	0.320 REF.		0.013 REF.	
D1	0.900	1.100	0.035	0.043	L	0.200	0.300	0.008	0.012

**Notes :** 1.Controlling dimension : millimeters.  
 2.Maximum lead thickness includes lead finish thickness, and minimum lead thickness is the minimum thickness of base material.  
 3.If there is any question with packing specification or packing method, please contact your local CYStek sales office.

**Material :**

- Lead :Pure tin plated.
- Mold Compound : Epoxy resin family, flammability solid burning class:UL94V-0.

**Important Notice:**

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of CYStek.
- CYStek reserves the right to make changes to its products without notice.
- CYStek **semiconductor products are not warranted to be suitable for use in Life-Support Applications, or systems.**
- CYStek assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.